



Online Sparse Bandits

David L. Saint-Pierre, Quentin Louveaux, Olivier Teytaud

► To cite this version:

David L. Saint-Pierre, Quentin Louveaux, Olivier Teytaud. Online Sparse Bandits. The 3rd Asian Conference on Machine Learning (ACML2011), Nov 2011, Taoyuan, Taiwan. hal-00642461

HAL Id: hal-00642461

<https://inria.hal.science/hal-00642461>

Submitted on 18 Nov 2011

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Online Sparse bandit

David L. St-Pierre¹, Quentin Louveaux¹, and Olivier Teytaud^{2,3}

¹ Department of Electrical Engineering and Computer Science, Faculty of Engineering, Liège University, Belgium

² TAO (Inria, Lri, Univ. Paris-Sud, UMR CNRS 8623), France

³ OASE Lab, National University of Tainan, Taiwan

What is a zero-sum Matrix Game (MG) ?

$M = K \times K$ matrix, coefficients in $[0,1]$

Player 1 chooses i in $\{1,2,3,\dots,K\}$

Player 2 chooses j in $\{1,2,3,\dots,K\}$

Player 1 gets reward M_{ij}

Player 2 gets reward $1 - M_{ij}$

Is solving a MG hard ?

= polynomial time (by linear programming)

best known coef 3.5

How to find approximate solutions ?

Grigoriadis & Khachiyan or Exp3 or Inf:

time $O(K \log K / \epsilon^2)$ with proba $\frac{1}{2}$

(Auer et al, Audibert et al, Grigoriadis et al)

Sparse versions ?

Very often, (x^*, y^*) is very sparse; plenty of 0's.

How to benefit from this ?

Algo. in Flory et al.:

1. Approximate solving by t iterations of EXP3
2. Remove small components
(keep only components $\geq (\max(tx))^{(4/5)} / t$)
3. Re-normalize
 \Rightarrow no proof

We propose the following online version \Rightarrow (EXP3 recalled below...)

Algorithm 1 EXP3 algorithm for iteration t with K arms.

```
Initialise  $\forall i, p(i) = \frac{1}{K}, n(i) = 0, S(i) = 0; t = 0$ 
while  $t < T$  do
  Arm  $i$  is chosen with probability  $p(i)$ 
   $n(i) \leftarrow n(i) + 1$ 
  Receive reward  $r$ 
   $t \leftarrow t + 1$ 
   $S_i$  modified by the update formula  $S_i \leftarrow S_i + r/p(i)$  (and  $S_j$  for  $j \neq i$  is not modified).
   $\forall i, p(i) = 1/(K\sqrt{t}) + (1 - 1/\sqrt{t}) \times \exp(S_i/\sqrt{t}) / \sum_j \exp(S_j/\sqrt{t})$ 
end while
return  $n$ 
```

What means “solving” a MG ?

Strategy x : probability distribution

on $\{1,2,3,\dots,K\}$

Strategy y : probability distribution

on $\{1,2,3,\dots,K\}$

Expected Reward:

$$R(x,y) =$$

$$E M_{ij} \mid (i,j) \sim x,y$$

Nash equilibrium:

$$(x^*, y^*) = \text{Nash}$$

\Leftrightarrow for all (x,y)

$$R(x, y^*) \geq R(x^*, y^*) \geq R(x^*, y)$$

Approximate solving ?

(x^*, y^*) ϵ -approximate Nash equilibrium if

for all (x,y) , $R(x, y^*) + \epsilon \geq R(x^*, y^*) \geq R(x^*, y) - \epsilon$

So what ?

There is a *offline* solution

(i.e. sparsity used at the end).

Can we use it online ?

Algorithm 3 onEXP3, an online EXP3 algorithm with a cut solely based on T .

```
Initialise  $\forall i, p(i) = \frac{1}{K}, n(i) = 0, S(i) = 0; t = 0$ 
while  $t < T$  do
  Arm  $i$  is chosen with probability  $p(i)$ 
   $n(i) \leftarrow n(i) + 1$ 
   $t \leftarrow t + 1$ 
  Receive reward  $r$ 
   $S_i$  modified by the update formula  $S_i \leftarrow S_i + r/p(i)$ 
   $\forall i, p(i) = 1/(K\sqrt{t}) + (1 - 1/\sqrt{t}) \times \exp(S_i/\sqrt{t}) / \sum_j \exp(S_j/\sqrt{t})$ 
  if  $x_i > \lceil \frac{t}{K} \rceil$  and  $x_i < (b_1 \times T^\delta \times (\frac{t}{T})^\beta)$  then
    Remove arm  $i$ 
  end if
  if every arm has been pruned then
    Use plain EXP3
  end if
  Renormalize:  $p = p / \sum_i p(i)$ 
end while
Execute the truncation TEXP3 as presented in 2.3
return  $n$ 
```

Conclusions ?

(i) it works (see numbers in paper)

(ii) theory missing

(iii) better (parameter-free ?) versions



\Leftarrow application: Urban Rivals
(free, you can test!)

Next application: Pokemon \Rightarrow

